



● 材质、表面处理



	SCS-GB 钢制	SCSS-GB 不锈钢制
螺纹部	SCM435 四氧化三铁保护膜(黑)	SUSXM7
球	SUJ2(硬度 55 - 60HRC)	SUS440C(硬度 55 - 60HRC)

- 球可灵活旋转9°。通过防反转结构牢牢地夹紧。
- 即使是铸造面等粗糙面，也能用齿纹球头牢牢地夹紧。
- 也生产螺纹公称直径、螺纹长度与表面处理等特殊的产品。请垂询客户中心。

单位: mm

型号 钢制	型号 不锈钢制	M(粗牙)	L	D	d	B	质量(g)
SCS-M4-6-GB	SCSS-M4-6-GB	M4	6	2.5	2	2	0.4
SCS-M4-10-GB	SCSS-M4-10-GB	M4	10	2.5	2	2	0.7
SCS-M4-16-GB	SCSS-M4-16-GB	M4	16	2.5	2	2	1
SCS-M5-8-GB	SCSS-M5-8-GB	M5	8	3	2.5	2.5	0.8
SCS-M5-12-GB	SCSS-M5-12-GB	M5	12	3	2.5	2.5	1.3
SCS-M5-20-GB	SCSS-M5-20-GB	M5	20	3	2.5	2.5	2.3
SCS-M6-10-GB	SCSS-M6-10-GB	M6	10	4	3.2	3	1.5
SCS-M6-16-GB	SCSS-M6-16-GB	M6	16	4	3.2	3	2.5
SCS-M6-20-GB	SCSS-M6-20-GB	M6	20	4	3.2	3	3.4
SCS-M6-25-GB	SCSS-M6-25-GB	M6	25	4	3.2	3	4
SCS-M8-10-GB	SCSS-M8-10-GB	M8	10	5.5	4.5	4	2.5
SCS-M8-12-GB	SCSS-M8-12-GB	M8	12	5.5	4.5	4	3.2
SCS-M8-20-GB	SCSS-M8-20-GB	M8	20	5.5	4.5	4	5.7
SCS-M8-25-GB	SCSS-M8-25-GB	M8	25	5.5	4.5	4	7.7
SCS-M8-30-GB	SCSS-M8-30-GB	M8	30	5.5	4.5	4	9
SCS-M10-12-GB	SCSS-M10-12-GB	M10	12	7	6	5	5
SCS-M10-16-GB	SCSS-M10-16-GB	M10	16	7	6	5	7
SCS-M10-20-GB	SCSS-M10-20-GB	M10	20	7	6	5	9.5
SCS-M10-25-GB	SCSS-M10-25-GB	M10	25	7	6	5	11
SCS-M10-35-GB	SCSS-M10-35-GB	M10	35	7	6	5	16
SCS-M12-16-GB	SCSS-M12-16-GB	M12	16	8.5	7.2	6	10
SCS-M12-20-GB	SCSS-M12-20-GB	M12	20	8.5	7.2	6	12.5
SCS-M12-30-GB	SCSS-M12-30-GB	M12	30	8.5	7.2	6	20
SCS-M12-40-GB	SCSS-M12-40-GB	M12	40	8.5	7.2	6	28
SCS-M16-20-GB	SCSS-M16-20-GB	M16	20	12	10.7	8	22
SCS-M16-25-GB	SCSS-M16-25-GB	M16	25	12	10.7	8	28
SCS-M16-35-GB	SCSS-M16-35-GB	M16	35	12	10.7	8	41
SCS-M16-50-GB	SCSS-M16-50-GB	M16	50	12	10.7	8	48

● 型号指定

SCS-M6-25-GB



无尘洗净・无尘包装 → P.xxxx

欢迎洽询

螺纹组合 → P.xxxx

可对应, 费用另计

螺纹切割 → P.xxxx

不可对应

防松动 → P.xxxx

可对应, 费用另计